



Brand of lasselsbergergroup

## Declaration of Performance No: G 13 01

- Unique product identification code:** Gxxxxxx except shaped elements (GTxxxxxx, GSxxxxx) and mosaics (GDMxxxxx)  
The type, series or another product identification code that enables its unique identification: glazed ceramic tile element with absorbing power up to 3.0% - Color Two and POOL tiles stated in the manufacturer's catalogue with allocated catalogue number.
- Intended use:** This group of products involves glazed tile elements for final finishing of internal and external floors and walls in areas that may be subject to frost and higher mechanical stress due to the specific characteristics of the individual products. The range of colours is diverse, with various types of décor in natural variation of tints, which are marked on the packaging in the field titled "Tint". It is necessary to pay attention to information provided on the packaging, accompanying leaflets and the manufacturer's technical catalogue before installation of the product (<https://www.rako.cz/cs/pro-odborniky>). It is necessary to observe the rules for application of construction chemicals that are stated in the concerned manuals.
- Manufacturer:** LASSELSBERGER, s.r.o., Adelova 2549/1, 320 00 Plzeň-Jižní Předměstí (Company ID No: 25238078) Czech Republic, Phone No.: +420 800 303 333, Fax: +420 378021 119, e-mail: [info@rako.cz](mailto:info@rako.cz)
- Authorised representative:** N/A
- Systems for assessing and verifying the performance stability of construction products:** System 4 (according to Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 and Annexes V, point 1.5 of 27 May 2014).
- In the case of the declaration of performance concerning construction products subject to the harmonized standard EN 14 411: 2012: name and identification number of notified body: irrelevant.
- The declared performances** listed in the statement apply to all commercial quality classes:

**Table 1: Declared product performances**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class A1 <sub>fl</sub> /A1	without testing (decree 96/603 EHS)
Breaking strength	Min. 900 N	EN 14 411:2012
Slipperiness	NPD*	
Durability for: - internal use - external use: freeze-thaw resistance	Pass Pass	
Thermal shock resistance	Pass	
Adhesion	- cementitious adhesives type C2: $\geq 1.0 \text{ N/mm}^2$	EN 14 411:2012
Release of dangerous substances: - Cadmium - Lead	max. $0.07 \text{ mg/dm}^2$ max. $0.8 \text{ mg/dm}^2$	
Assessment of natural radionuclide content	max. index of mass activity 1.0	

\* No Performance Determined - NPD (No Performance Determined)

The products comply with the requirements for the content of natural radionuclides according to Decree No. 422/2016 Coll., as amended. The products further comply with the requirements for leachability of Cd, Pb within the meaning of EN 14 411:2012 and can be used on worktops and wall surfaces where food is prepared and where food gets in direct contact with the glazed surface of the tile element.



Brand of **lasselsberger**group

8. The relevant technical documentation and/or specific technical documentation:

This declaration of performance is in compliance with Regulation (EU) No. 305/2011 issued on the exclusive liability of the above-stated manufacturer. The performances of the above-stated product complies with the set of declared performances. According to Regulation REACH No 1907/2006, the ceramic tile elements are objects that do not emit any chemical substances.

Signed on behalf of the manufacturer and in its name:  
November 10th, 2020, Pilsen  
Replaces the declaration dated September 1st, 2019



Ing. Zuzana Fajfrová, Quality Manager

**Additional product information:**

**Table 2: Values of the slip resistance performances of glazed sintered ceramic tile elements according to CEN/TS 16165:**

Name of the method	Friction coefficient		DIN 51 130	DIN 51 097
	μ in dry conditions	μ in wet conditions		
Type of surface (series) and the product ID code			R	(A, B, C)
Anti-slide embossed surface (GRSxxxxx)	≥ 0.6	≥ 0.5	R10	B
Anti-slide embossed surface (GRNxxxxx)	≥ 0.6	≥ 0.5	R10	B
Anti-slide surface (GAKxxxxx)	≥ 0.6	≥ 0.5	R10	B
Anti-slide embossed surface, C (GRHxxxxx)	≥ 0.7	≥ 0.5	NPD*	C
Anti-slide surface (GAFxxxxx)	≥ 0.6	≥ 0.5	R10	B
Smooth surface (GAAxxxxx , GATxxxxx) matte	≥ 0.5	≥ 0.3	NPD*	NPD*
Samba (GAT3Bxxx)	≥ 0.6	≥ 0.5	R9	A

\* No Performance Determined - NPD (No Performance Determined)