



**Declaration of performance
No. BC1 161 J0V**

1. Unique identification code of the product-type : **BC1 161 J0V**
2. **MO 35 QUICK**
H – factory 378 09 Nová Ves nad Lužnicí
3. **General purpose rendering / plastering mortar (GP) according to EN 998-1.**
4. **LB Cemix, s.r.o., Tovární ulice č.p. 36, 373 12 Borovany, Czech Republic**
5. ---
6. System of assessment and verification of constancy of performance of the construction product : **4**
7. ---
8. ---

9.

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class A1	EN 13501-1+A1:2009
Adhesive strength	min. 0,3 N/mm ² – FP: B	EN 998-1:2010
Capillary water absorption	W 1	EN 998-1:2010
Water vapour permeability coefficient	μ 35	EN 998-1:2010
Coefficient of thermal conductivity	(λ _{10, dry}) 1,42 W/m.K *)	EN 998-1:2010
Durability – number of cycles **)	min. 15	EN 998-1:2010

*) tabulated value

***) testing of frost resistance of mortar according to ČSN 72 2452

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by : **Petr Semera, Production and Technical Director, LB Cemix, s.r.o., Borovany**

Borovany, 1st July 2013